

PRE-INSULATED BULLET CONNECTORS | Terminals


QUICK CONNECTORS



Closed End Connectors

Closed end connectors.

Temperature Range: -40°C to 105°C
Material: Tin Plated Electrolytic Copper / Vinyl
Voltage: 600V
Colour: Clear



Code	Range mm ²	ID (A)	Length (L2)	Width (W)
CECS	0.5 - 1.5	2.6	18.2	5.5
CECM	1.5 - 2.5	3.3	20.0	8.0
CECL	4.0 - 6.0	4.5	25.5	11.0



Quick Splice / Connectors

Quick splice connectors.

Temperature Range: -40°C to 105°C
Material: Tin Plated Electrolytic Copper / Vinyl
Voltage: 600V
Colour: Red, Blue, Yellow




Code	Colour	Range mm ²	Length (L2)	Width (W)
RCT	Red	0.5 - 1.5	29.0	19.0
BCT	Blue	1.5 - 2.5	29.0	19.0
YCT	Yellow	4.0 - 6.0	35.5	20.4



Heat Shrinkable Solder Sleeve

Heat shrinkable solder sleeve.

Temperature Range: -45°C to 125°C
Shrinkable Temp: +125°C to 180°C
Material: Tin Plated Electrolytic Copper / Vinyl
Colour: Red, Blue, Yellow, White
Voltage: 600V
Standards: DIN 46288 Part 4



Code	Colour	Range mm ²	Length (L2)	Min (A)	Wire Min	Wire Max
HSSOLW	White	0.25-034	26.0	1.7	0.4	1.7
HSSOLR	Red	0.5-1.5	40.0	2.7	1.3	2.7
HSSOLB	Blue	1.5-2.5	40.0	4.5	1.8	4.5
HSSOLY	Yellow	4.0-6.0	40.0	6.0	2.8	6.0