

PVC SLEEVING

PVC Sleevings

Coloured PVC Sleevings

Our RoHS compliant high grade PVC flexible Earth Sleevings is manufactured from premium virgin grade compound in a wide range of sizes. Standard nominal wall size is 0.5mm, other sizes are available to order. Supplied with green and yellow stripes for use in earth identification and solid colour for electrical contracting purposes. Supplied in continuous 100m coils. Some sizes are available supplied on reels, please contact us for more information



Green/Yellow and Coloured PVC Sleevings

Dielectric Strength: 20 kV/mm min

Temperature Range: -20°C to 70°C

Elongation at Break: 220% min

Insulation Resistance: 10¹⁰ ohm/cm

Hardness: BSS20-30

Flammability: Self-extinguishing in 30 seconds

Standards: BS 2848/3/85T

Material: PVC

Colour: Green/Yellow, Black, Blue, Brown, Yellow, Grey, Red, Green, White



Code	Internal Diameter	To Cover Cable Size mm ²	Coil Length (m)
PVC-2.0-G/Y	2.0		100
PVC-3.0-G/Y	3.0	0.5-0.75	100
PVC-4.0-G/Y	4.0	1.5-2.5	100
PVC-6.0-G/Y	6.0	6.0	100
PVC-8.0-G/Y	8.0	10.0	100
PVC-10.0-G/Y	10.0	16.0-25.0	100

Code	Internal Diameter	To Cover Cable Size mm ²	Coil Length (m)
PVC-2.0-*	2.0		100
PVC-3.0-*	3.0	0.5-0.75	100
PVC-4.0-*	4.0	1.5-2.5	100
PVC-6.0-*	6.0	6.0	100
PVC-8.0-*	8.0	10.0	100
PVC-10.0-*	10.0	16.0-25.0	100

How To Order



Code prefix

Size

Colour: GY= Green/Yellow
 Black
 B = Black
 BL = Blue
 BR = Brown
 Y = Yellow

G = Grey
 GR = Green
 R = Red
 W = White