

METALLIC CABLE GLANDS | Cable Glands

BRASS CABLE GLANDS

Brass IP68 Glands PG

- Alternative PG range of brass cable glands with alternate cable range.


Standards: EN 50262

Protection: IP68 10 bar (150 PSI)

Temperature Range: -40°C to 100°C (static) (120° Instantaneous)

Material (Gland): Nickel-Plated Brass

Material (Seal): NBR Seal and EPDM O-Ring



Code	Cable Range (B)		Entry Thread Size	Gland		
	Min	Max		Length (L1)	Length (L2)	A/F
NP-IP68PG7	3.0	6.0	PG7 x 1.27	10.0	26.0	14.0
NP-IP68PG9	5.5	9.0	PG9 x 1.41	10.0	27.0	18.0
NP-IP68PG11	5.5	9.0	PG11 x 1.41	10.0	27.0	22.0
NP-IP68PG13.5	8.5	12.5	PG13.5 x 1.41	10.0	28.0	22.0
NP-IP68PG16	8.5	12.5	PG16 x 1.41	10.0	28.0	25.0
NP-IP68PG21	12.0	16.5	PG21 x 1.59	10.0	30.0	33.0
NP-IP68PG29	16.0	21.0	PG29 x 1.59	13.0	36.0	43.0
NP-IP68PG36	19.5	27.0	PG36 x 1.59	13.0	42.0	52.0
NP-IP68PG42	26.0	35.0	PG42 x 1.59	14.0	90.0	60.0
NP-IP68PG48	32.0	47.0	PG48 x 1.59	14.0	49.0	68.0



Locknuts Supplied Separately p.89



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution

Cable Glands
Accs.
Wiring Terminals
Tube Lugs
Tooling
Earthing/Lightning
Joining
Heat-shrink
Junction Boxes
Cable Cleats
Cable Ties
MCC Cable
Conduit
Fixing & Security