

PRE-INSULATED RING TERMINALS | Terminals

PRE-INSULATED CRIMP TERMINALS



Pre-Insulated Fork Terminals


Fork terminals, are designed to behave similarly to ring terminals but with a fork shaped end that allows the terminal to be installed or removed in tight spaces.

Temperature Range: -10°C to 75°C

Material: Tin Plated Electrolytic Copper / Vinyl

Voltage: 600V

Colour: Red, Blue, Yellow



Code	Colour	Range mm ²	ID (A)	ID (B)	Length (L1)	Length (L2)	Width (W)
RF32	Red	0.5-1.5	1.7	3.3	11.0	21.0	5.7
RF37		0.5-1.5	1.7	3.8	11.0	21.0	5.7
RF43		0.5-1.5	1.7	4.4	11.0	21.0	6.4
RF53		0.5-1.5	1.7	5.4	11.0	21.0	8.1
RF64		0.5-1.5	1.7	6.6	11.0	21.0	9.5
BF32		Blue	1.5-2.5	2.3	3.3	11.0	21.0
BF37	1.5-2.5		2.3	3.8	11.0	21.0	5.7
BF43	1.5-2.5		2.3	4.4	11.0	21.0	6.4
BF53	1.5-2.5		2.3	5.4	11.0	21.0	7.9
BF64	1.5-2.5		2.3	6.6	11.0	21.0	9.3
YF37	Yellow		4.0-6.0	3.4	3.8	12.5	25.5
YF43		4.0-6.0	3.4	4.4	12.5	25.5	8.3
YF53		4.0-6.0	3.4	5.4	12.5	25.5	9.0
YF64		4.0-6.0	3.4	6.6	12.5	25.5	9.0



Pre-Insulated Blade Terminals


A blade connector is a type of single wire connection using a flat conductive blade which is inserted into a blade receptacle.

Temperature Range: -10°C to 75°C

Material: Tin Plated Electrolytic Copper / Vinyl

Voltage: 600V

Colour: Red, Blue, Yellow



Code	Colour	Range mm ²	ID (A)	Length (L1)	Length (L2)	Width (W)
RB2318	Red	0.5-1.5	1.7	18.0	28.0	2.2
BB2318	Blue	1.5-2.5	2.3	18.0	28.0	2.2
YB2810	Yellow	4.0-6.0	3.4	10.0	23.0	2.8



Pre-Insulated Pin Terminals


Wire Pin Terminals offer quick and easy connections in applications where set screws or clamps are used to make electrical contact with the wire

Temperature Range: -10°C to 75°C

Material: Tin Plated Electrolytic Copper / Vinyl

Voltage: 600V

Colour: Red, Blue, Yellow



Code	Colour	Range mm ²	ID (A)	Length (L1)	Length (L2)	Width (W)
RP1912	Red	0.5-1.5	1.7	12.0	21.8	1.9
BP1912	Blue	1.5-2.5	2.3	12.0	21.8	1.9
YP2914	Yellow	4.0-6.0	3.4	14.0	26.0	2.8