



Multi-Reel

Multi-Reel PVC Sleeving

The PVC Multi Reel is designed with electricians in mind. It is supplied on one reel, which is split into 3 sections. Our RoHS compliant high grade PVC flexible Earth Sleeving is manufactured from premium virgin grade compound and is available in diameters of 2.0mm, 3.0mm or 4.0mm. The 2.0mm and 3.0mm contains 20 metres Blue & Brown Sleeving and 60 metres Green/Yellow sleeving. The 4.0mm contains 10 metres Blue & Brown Sleeving and 40 metres Green/Yellow sleeving.

Green/Yellow and Coloured PVC Sleeving

Dielectric Strength: 20 kV/mm min
Temperature Range: -20°C to 70°C
Elongation at Break: 220% min
Insulation Resistance: 10¹⁰ ohm/cm
Hardness: BSS20-30
Flammability: Self-extinguishing in 30 seconds
Standards: BS 2848/3/85T
Material: PVC
Colour: Green/Yellow, Blue & Brown



Code	Internal Diameter	To Cover Cable Size mm ²	Coil Length (m)	
			Blue & Brown	Green/Yellow
PVC-MR-2.0	2.0		20	60
PVC-MR-3.0	3.0	0.5-0.75	20	60
PVC-MR-4.0	4.0	1.5-2.5	10	40

Push Back Braided Sleeving

Braided sleeving is a range of lightweight, self-fitting, flexible sleeving that provides tough protection for bundles of cables up to a maximum diameter of 140mm. Low smoke, low toxicity and halogen free with an expansion ratio of 3:1.

Material: Heat Stabilised Polyester
Monofilament: Polyester Size 0.22mm
Melting Point: +250°C
Limiting Oxygen Index: 34%
Continuous Temperature: -50°C to +150°C
Flammability: CEI 322-1, FMVSS 302 (Type A) 12 / NF F 16-101



Code	Diameter (mm)	Reel Quantity
BS5/100-B	5 - 10	100
BS10/100-B	8 - 14	100
BS15/50-B	12 - 20	50
BS20/50-B	18 - 25	50
BS25/30-B	22 - 30	30
BS30/25-B	26 - 35	25
BS40/25-B	35 - 45	25
BS50/25-B	45 - 55	25

Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution