

# Terminals | HEAT SHRINKABLE SPADE TERMINALS

## HEAT SHRINKABLE INSULATED TERMINALS

# Heat Shrinkable Spade Terminals

Made from oxygen-free high conductivity copper, these terminals are electro-tin plated for excellent conductivity and resistance to corrosion. Push-on terminals are made from brass, the insulated types have an additional internal copper sleeve, ensuring insulation support and a good crimp joint.




### Heat Shrinkable Male Spade Terminals

Heat shrinkable male spade terminals.

**Temperature Range:** -40°C to 105°C

**Material:** Tin Plated Electrolytic Copper / Vinyl

**Colour:** Red, Blue, Yellow



Code	Colour	Range mm <sup>2</sup>	Tab	ID (A)	Length (L1)	Length (L2)	Width (W)
HSRTAB63	Red	0.5-1.5	6.35	1.7	10.0	35.0	6.35
HSBTAB63	Blue	1.5-2.5	6.35	2.3	10.0	35.0	6.35
HSYTAB63	Yellow	4.0-6.0	6.35	3.4	10.0	36.0	6.35


### Heat Shrinkable Female Spade Terminals

Heat shrinkable female spade terminals.

**Temperature Range:** -40°C to 105°C

**Material:** Tin Plated Electrolytic Copper / Vinyl

**Colour:** Red, Blue, Yellow



Code	Colour	Range mm <sup>2</sup>	ID (A)	Length (L1)	Length (L2)	Width (W)
HSRFS63	Red	0.5-1.5	1.7	8.0	33.0	6.5
HSBFS63	Blue	1.5-2.5	2.3	8.0	33.0	6.5
HSYFS63	Yellow	4.0-6.0	3.4	8.0	34.0	6.5