

WRPS Seal kits



NOTES:
 WRPS seals (commonly known as standard seals) are designed to be used in conjunction with Wrexham Mineral Cables glands. Manufactured and tested to BS EN 60702-2:2002. For ambient service temperatures of -20°C to 105°C. Dependent on the cable size the pots are supplied in 20mm 25mm 32mm and 40mm

The WRPS seal kit contains the following as standard	
ITEM DESCRIPTION	QTY
WRPS POTS	20mm pots x 10, 25 32 & 40mm pots x 2
SEAL OR STUB CAPS (SIZE DEPENDANT)	20mm pots x 10, 25 32 & 40mm pots x 2
WRMX SEALING COMPOUND	20mm pots x 3 sticks, 25 32 & 40mm pots x 2
PVC SLEEVING	Dependent on cores - either 2 or 3 hanks of 1.5m

Heavy Duty Cables			
CABLE REFERENCE	SEAL NEEDED	CABLE REFERENCE	SEAL NEEDED
1H2.5	WRPS1H2.5	3H2.5	WRPS3H2.5
1H4	WRPS1H4	3H4	WRPS3H4
1H6	WRPS1H6	3H6	WRPS3H6
1H10	WRPS1H10	3H10	WRPS3H10
1H16	WRPS1H16	3H16	WRPS3H16
1H25	WRPS1H25	3H25	WRPS3H25
1H35	WRPS1H35	4H1.5	WRPS4H1.5
1H50	WRPS1H50	4H2.5	WRPS4H2.5
1H95	WRPS1H95	4H4	WRPS4H4
1h120	WRPS1H120	4H6	WRPS4H6
1H150	WRPS1H150	4H10	WRPS4H10
1H185	WRPS1H185	4H16	WRPS4H16
1H240	WRPS1H240	4H25	WRPS4H25
1H300	WRPS1H300	7H1.5	WRPS7H1.5
2H1.5	WRPS2H1.5	7H2.5	WRPS7H2.5
2H2.5	WRPS2H2.5	12H1.5	WRPS12H1.5
2H4	WRPS2H4	12H2.5	WRPS12H2.5
2H6	WRPS2H6	19H1.5	WRPS19H1.5
2H10	WRPS2H10		
3H1.5	WRPS3H1.5		

Light Duty Cables	
CABLE REFERENCE	SEAL NEEDED
2L1	WRPS2L1
2L1.5	WRPS2L1.5*
2L2.5	WRPS2L2.5*
2L4	WRPS2L4
3L1	WRPS3L1
3L1.5	WRPS3L1.5*
3L2.5	WRPS3L2.5*
4L1	WRPS4L1
4L1.5	WRPS4L1.5*
4L2.5	WRPS4L2.5*
7L1.5	WRPS7L1.5
7L2.5	WRPS7L2.5

Also used in twisted range (T) cables