

Metric-Metric Industrial Reducers

- ISO Metric range.
- Application; Machines, Devices, Housings, Panels

Standards: EN 50262

Protection: IP54

IP66 (if fitted with sealing washer)

Temperature Range: -60°C to 200°C

Material: Nickel Plated Brass



Code	Entry Thread		Thread Length	
	Male	Female	Male (L1)	A/F
RM16M12S	M16 x 1.5	M12 x 1.5	10.0	18.0
RM20M12S	M20 x 1.5	M12 x 1.5	13.0	22.0
RM20M16S	M20 x 1.5	M16 x 1.5	13.0	22.0
RM25M16S	M25 x 1.5	M16 x 1.5	13.0	27.0
RM25M20S	M25 x 1.5	M20 x 1.5	13.0	27.0
RM32M20S	M32 x 1.5	M20 x 1.5	13.0	34.0
RM32M25S	M32 x 1.5	M25 x 1.5	13.0	34.0
RM40M20S	M40 x 1.5	M20 x 1.5	13.0	43.0
RM40M25S	M40 x 1.5	M25 x 1.5	13.0	43.0
RM40M32S	M40 x 1.5	M32 x 1.5	13.0	43.0
RM50M20S	M50 x 1.5	M20 x 1.5	13.0	53.0
RM50M25S	M50 x 1.5	M25 x 1.5	13.0	53.0
RM50M32S	M50 x 1.5	M32 x 1.5	13.0	53.0
RM50M40S	M50 x 1.5	M40 x 1.5	13.0	53.0
RM63M20S	M63 x 1.5	M20 x 1.5	13.0	66.0
RM63M25S	M63 x 1.5	M25 x 1.5	13.0	66.0
RM63M32S	M63 x 1.5	M32 x 1.5	13.0	66.0
RM63M40S	M63 x 1.5	M40 x 1.5	13.0	66.0
RM63M50S	M63 x 1.5	M50 x 1.5	13.0	66.0
RM75M63S	M75 x 1.5	M63 x 1.5	13.0	78.0

PG-Metric Industrial Reducers

- PG-ISO Metric range.

Code	Entry Thread		Thread Length	
	Male	Female	Male (L1)	A/F
RPG16M20S	PG16 x 1.41	M20 x 1.5	13.0	24.5
RPG21M20S	PG21 x 1.59	M20 x 1.5	13.0	30.3
RPG21M25S	PG21 x 1.59	M25 x 1.5	13.0	30.3
RPG29M20S	PG29 x 1.59	M20 x 1.5	13.0	39.0
RPG29M25S	PG29 x 1.59	M25 x 1.5	13.0	39.0
RPG29M32S	PG29 x 1.59	M32 x 1.5	13.0	39.0
RPG36M25S	PG36 x 1.59	M25 x 1.5	13.0	50.0
RPG36M32S	PG36 x 1.59	M32 x 1.5	13.0	50.0
RPG36M40S	PG36 x 1.59	M40 x 1.5	13.0	50.0
RPG42M32S	PG42 x 1.59	M32 x 1.5	13.0	57.0
RPG42M40S	PG42 x 1.59	M40 x 1.5	13.0	57.0
RPG42M50S	PG42 x 1.59	M50 x 1.5	13.0	57.0
RPG48M32S	PG48 x 1.59	M32 x 1.5	13.0	62.3
RPG48M40S	PG48 x 1.59	M40 x 1.5	13.0	62.3
RPG48M50S	PG48 x 1.59	M50 x 1.5	13.0	62.3



Sealing Washers
Supplied Separately p.92



Call the Remora sales team at **01226 352 000**

Challenge us - We find a solution