

WRPSL Earth Tail Seal kits



The WRPSL seal kit contains the following as standard	
ITEM DESCRIPTION	QTY
WRPSL POTS WITH 150mm EARTH TAIL	20mm pots x 10, 25 32 & 40mm pots x 2
SEAL OR STUB CAPS (SIZE DEPENDENT)	20mm pots x 10, 25 32 & 40mm pots x 2
WRMX SEALING COMPOUND	20mm pots x 3 sticks, 25 32 & 40mm pots x 2
PVC SLEEVING (BLACK)	Dependent on cores - either 2 or 3 hanks of 1.5m
PVC SLEEVING (GREEN & YELLOW)	Dependent on cores - either 1 or 2 hanks of 1.5m

WRPSL EARTH TAIL SEAL KIT

Fire Resistant Cable Accessories

NOTES:

WRPSL seals (commonly known as Earth Tail seals) are designed to be used in conjunction with Wrexham Mineral Cables glands. Manufactured and tested to BS EN 60702-2:2002. For ambient service temperatures of -20°C to 105°C Earth Tail Seals have an integrated earth tail (150mm long), crimped and soldered into the base of the brass pot.

This provides earth continuity or sheath bonding into the application for cable conductor sizes up to and including 50mm² (Excluding those with 12 and 19 conductors) As per the British IEC regulations our Earth tail seals are no less than half the size of the conductor and meet latest wiring regulations.

Heavy Duty Cables			
CABLE REFERENCE	SEAL NEEDED	CABLE REFERENCE	SEAL NEEDED
1H2.5	WRPSL1H2.5	3H4	WRPSL3H4
1H4	WRPSL1H4	3H6	WRPSL3H6
1H6	WRPSL1H6	3H10	WRPSL3H10
1H10	WRPSL1H10	3H16	WRPSL3H16
1H16	WRPSL1H16	3H25	WRPSL3H25
1H25	WRPSL1H25	4H1.5	WRPSL4H1.5
1H35	WRPSL1H35	4H2.5	WRPSL4H2.5
1H50	WRPSL1H50	4H4	WRPSL4H4
2H1.5	WRPSL2H1.5	4H6	WRPSL4H6
2H2.5	WRPSL2H2.5	4H10	WRPSL4H10
2H4	WRPSL2H4	4H16	WRPSL4H16
2H6	WRPSL2H6	4H25	WRPSL4H25
2H10	WRPSL2H10	7H1.5	WRPSL7H1.5
3H1.5	WRPSL3H1.5	7H2.5	WRPSL7H2.5
3H2.5	WRPSL3H2.5		

Light Duty Cables	
CABLE REFERENCE	SEAL NEEDED
2L1	WRPSL2L1
2L1.5	WRPSL2L1.5
2L2.5	WRPSL2L2.5
2L4	WRPSL2L4
3L1	WRPSL3L1
3L1.5	WRPSL3L1.5
3L2.5	WRPSL3L2.5
4L1	WRPSL4L1
4L1.5	WRPSL4L1.5
4L2	WRPSL4L2
4L2.5	WRPSL4L2.5

Above 50mm² single core only standard seal (WRPS) available
 12 & 19 core only available as standard seal (WRPS)