

# Accessories | HEX HEAD STOPPING PLUGS

## INDUSTRIAL AREA METRIC

Ident & Wiring Term  
Copper Lugs  
Heatshrink Repair  
Cable Joining  
Junction Boxes  
Flexible Conduit  
Cable Glands  
Gland Accs.  
Cable Cleats  
Earthing Lightning  
MCC Cable  
Cable Ties & Acc  
Tooling & Cable Prep  
Fixing & Security



### Hex Head Nylon Stopping Plugs

Remora industrial Hex Head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes.

**Protection:** IP56

IP66 (if fitted with sealing washer)

**Temperature Range:** -20°C to 80°C(static) 120°(temp)

**Material:** PA6 (Nylon) UL94 V2

**Colour:** Black or White



Black Code	White Code	Entry Thread	Thread Length (L1)	A/F	A/C
NSTP16	NSTP16W	M16 x 1.5	12.0	19.0	22.0
NSTP20	NSTP20W	M20 x 1.5	12.0	23.0	26.0
NSTP25	NSTP25W	M25 x 1.5	13.5	28.0	32.0
NSTP32	NSTP32W	M32 x 1.5	13.5	36.0	41.0

### Hex Head Brass Stopping Plugs

Remora industrial Hex Head stopping plugs are designed as a cost effective permanent solution for blanking unused pre-threaded holes.



**Standards:** EN 50262

**Protection:** IP54

IP66 (if fitted with sealing washer)

**Temperature Range:** -60°C to 200°C

**Material:** Nickel Plated Brass



Code	Entry Thread	Thread Length (L1)	A/F
STPH16	M16 x 1.5	12.0	18.0
STPH20	M20 x 1.5	13.0	22.0
STPH25	M25 x 1.5	13.0	27.0
STPH32	M32 x 1.5	16.0	34.0
STPH40	M40 x 1.5	18.0	43.0
STPH50	M50 x 1.5	18.0	54.0
STPH63	M63 x 1.5	18.0	68.0
STPH75	M75 x 1.5	20.0	80.0



Sealing Washers  
Supplied Separately p.180