



Emperor

Single or Dual-Fixing

The Emperor range offers the ultimate protection against the harshest conditions, and its unique design means it can be quickly installed. Manufactured in Type 316L Stainless Steel, Emperor cleats are available in multiple sizes with range-taking capability, to suit single cables.

To protect and cushion the cables during short circuit conditions, the cleat is supplied with an integral Low Smoke and Fume Polymeric liner and base pad. We recommend that the Emperor is fixed using either two 10mm bolts, or a single 12mm bolt. Alternative bolt recommendations on request.

316L Stainless Steel Single Cleat

- Superior strength tensile strength
- Excellent weathering and corrosion resistance
- Excellent stiffness


Standards: European Standard IEC 61914:2015
ABS DNV Type Approved, UL Listed

Max Short-Circuit:

149kA	600mm Spacing
195kA	300mm Spacing
235kA	225mm Spacing

Temperature Range: -40°C to 60°C

Material: 316L Stainless Steel / Polymeric Liner/Base Pad



Code	Single Cable Range		Dimensions				D1 + D2	Fixing Holes
	Min	Max	(A)	(B)	(C)	(E)		
ES32-39	32.0	39.0	89.0	91.0	54.0	25.0	2xM10 + 1xM12	
ES37-45	37.0	45.0	93.0	96.0	54.0	25.0	2xM10 + 1xM12	
ES44-52	44.0	52.0	98.0	99.0	54.0	25.0	2xM10 + 1xM12	
ES51-59	51.0	59.0	102.0	103.0	54.0	25.0	2xM10 + 1xM12	
ES58-66	58.0	66.0	101.0	109.0	54.0	25.0	2xM10 + 1xM12	
ES65-73	65.0	73.0	103.0	111.0	54.0	25.0	2xM10 + 1xM12	
ES73-85	73.0	85.0	112.0	135.0	54.0	50.0	2xM10 + 1xM12	
ES84-94	84.0	94.0	135.0	135.0	54.0	50.0	2xM10 + 1xM12	
ES94-118	94.0	118.0	150.0	160.0	54.0	50.0	2xM10 + 1xM12	
ES118-130	118.0	130.0	160.0	175.0	54.0	75.0	2xM10 + 1xM12	
ES127-150	127.0	150.0	180.0	180.0	54.0	75.0	2xM10 + 1xM12	