



# Accessories | HAZARDOUS AREA ADAPTORS

## BRASS ADAPTORS METRIC & PG



### Metric-Metric Hazardous Adaptors

Enlarges housing entry thread.

- ISO Metric range.

• Application: Hazardous Area, Machines, Devices, Housings, Panels

**Standards:** IECEx: Ex db I Mb / Ex eb I Mb / Ex db IIC Gb / Ex eb IIC Gb

ATEX: I M2 Ex db I Mb / Ex eb I Mb, II 2 GD Ex db IIC Gb

**Protection:** IP66 / IP68 (2m cont.) BS EN 62444

**Temperature Range:** -20°C to 95°C (-60°C to 160°C with High Temp Gasket)

**Material:** Brass or Nickel Plated Brass (Marine Grade)



Code	Entry Thread		Thread Length		A/F	A/C	Hex Length Min (G)
	Male	Female	Male (L1)	Female (F)			
AM16M20E-UN	M16 x 1.5	M20 x 1.5	15.0	15.0	27.0	30.4	21.0
AM16M25E-UN	M16 x 1.5	M25 x 1.5	15.0	15.0	27.0	30.4	21.0
AM20M25E-UN	M20 x 1.5	M25 x 1.5	15.0	15.0	32.0	36.0	21.0
AM20M32E-UN	M20 x 1.5	M32 x 1.5	15.0	15.0	32.0	36.0	21.0
AM25M32E-UN	M25 x 1.5	M32 x 1.5	15.0	15.0	38.0	42.8	21.0
AM25M40E-UN	M25 x 1.5	M40 x 1.5	15.0	15.0	38.0	42.8	21.0
AM32M40E-UN	M32 x 1.5	M40 x 1.5	15.0	15.0	50.0	56.3	21.0
AM32M50E-UN	M32 x 1.5	M50 x 1.5	15.0	15.0	50.0	56.3	21.0
AM40M50E-UN	M40 x 1.5	M50 x 1.5	15.0	15.0	60.0	67.5	21.0
AM40M63E-UN	M40 x 1.5	M63 x 1.5	15.0	15.0	60.0	67.5	21.0
AM50M63E-UN	M50 x 1.5	M63 x 1.5	15.0	15.0	70.0	78.8	21.0
AM50M75E-UN	M50 x 1.5	M75 x 1.5	15.0	15.0	70.0	78.8	21.0
AM63M75E-UN	M63 x 1.5	M75 x 1.5	15.0	15.0	80.0	90.0	21.0

- For Nickel Plated remove -UN when ordering

### PG-Metric Hazardous Adaptors

Enlarges housing entry thread.

- PG - ISO Metric range.

• Application: Hazardous Area, Machines, Devices, Housings, Panels

**Standards:** IECEx: Ex db I Mb / Ex eb I Mb / Ex db IIC Gb / Ex eb IIC Gb

ATEX: I M2 Ex db I Mb / Ex eb I Mb, II 2 GD Ex db IIC Gb

**Protection:** IP66 / IP68 (2m cont.) BS EN 62444

**Temperature Range:** -20°C to 95°C (-60°C to 160°C with High Temp Gasket)

**Material:** Brass or Nickel Plated Brass (Marine Grade)



Code	Entry Thread		Thread Length		A/F	A/C	Hex Length Min (G)
	Male	Female	Male (L1)	Female (F)			
APG9M20E-UN	PG9	M20 x 1.5	17.0	18.0	27.0	30.4	21.0
APG11M20E-UN	PG11	M20 x 1.5	17.0	18.0	27.0	30.4	21.0
APG13M20E-UN	PG13.5	M20 x 1.5	17.0	18.0	27.0	30.4	21.0
APG13M25E-UN	PG13.5	M25 x 1.5	17.0	18.0	30.0	33.8	21.0
APG16M25E-UN	PG16	M25 x 1.5	17.0	18.0	32.0	36.0	21.0
APG21M32E-UN	PG21	M32 x 1.5	17.0	18.0	36.0	42.8	21.0
APG29M40E-UN	PG29	M40 x 1.5	17.0	21.0	50.0	56.3	21.0
APG36M50E-UN	PG36	M50 x 1.5	17.0	21.0	70.0	78.8	24.0
APG42M63E-UN	PG42	M63 x 1.5	17.0	21.0	70.0	78.8	24.0
APG48M63E-UN	PG48	M63 x 1.5	17.0	21.0	70.0	78.8	24.0

- For Nickel Plated remove -UN when ordering