

Brass GripLoc® Glands Metric

- Standard Metric range of brass cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.


Standards: EN 50262

Protection: IP69K / IP68 10 bar (150 PSI)

Temperature Range: -40°C to 100°C (static) (120° temp)

Material (Gland): Nickel-Plated Brass

Material (Seal): NBR Seal and EPDM O-Ring



| Code | Cable Range (B) | | Entry Thread | | Gland | |
|-----------------|-----------------|------|--------------|-------------|-------------|------|
| | Min | Max | Size | Length (L1) | Length (L2) | A/F |
| GripLoc-BR-M12 | 2.0 | 5.0 | M12 x 1.5 | 6.5 | 25.5 | 14.0 |
| GripLoc-BR-M16 | 5.0 | 10.0 | M16 x 1.5 | 6.0 | 27.0 | 19.0 |
| GripLoc-BR-M20 | 6.0 | 12.0 | M20 x 1.5 | 6.0 | 29.0 | 22.0 |
| GripLoc-BR-M20L | 10.0 | 14.0 | M20 x 1.5 | 6.0 | 30.0 | 24.0 |
| GripLoc-BR-M25 | 13.0 | 18.0 | M25 x 1.5 | 7.0 | 32.0 | 30.0 |
| GripLoc-BR-M32 | 18.0 | 25.0 | M32 x 1.5 | 8.0 | 39.0 | 40.0 |
| GripLoc-BR-M40 | 22.0 | 32.0 | M40 x 1.5 | 8.0 | 45.0 | 50.0 |
| GripLoc-BR-M50 | 32.0 | 38.0 | M50 x 1.5 | 9.0 | 46.0 | 57.0 |
| GripLoc-BR-M63 | 37.0 | 44.0 | M63 x 1.5 | 10.0 | 48.0 | 68.0 |

Brass GripLoc® Glands Metric - Long Thread

- Long Thread range of brass cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.


Standards: EN 50262

Protection: IP69K / IP68 10 bar (150 PSI)

Temperature Range: -40°C to 100°C (static) (120° temp)

Material (Gland): Nickel-Plated Brass

Material (Seal): NBR Seal and EPDM O-Ring



Locknuts Supplied Separately p.89

Multi-Hole Seals p.29



| Code | Cable Range (B) | | Entry Thread | | Gland | |
|--------------------|-----------------|------|--------------|-------------|-------------|------|
| | Min | Max | Size | Length (L1) | Length (L2) | A/F |
| GripLoc-BR-LT-M12 | 2.0 | 5.0 | M12 x 1.5 | 10.0 | 29.0 | 14.0 |
| GripLoc-BR-LT-M16 | 4.0 | 8.0 | M16 x 1.5 | 10.0 | 31.0 | 19.0 |
| GripLoc-BR-LT-M20 | 6.0 | 12.0 | M20 x 1.5 | 10.0 | 33.0 | 22.0 |
| GripLoc-BR-LT-M20L | 10.0 | 14.0 | M20 x 1.5 | 10.0 | 34.0 | 24.0 |
| GripLoc-BR-LT-M25 | 13.0 | 18.0 | M25 x 1.5 | 12.0 | 37.0 | 30.0 |
| GripLoc-BR-LT-M32 | 18.0 | 25.0 | M32 x 1.5 | 12.0 | 43.0 | 40.0 |
| GripLoc-BR-LT-M40 | 22.0 | 32.0 | M40 x 1.5 | 15.0 | 52.0 | 50.0 |
| GripLoc-BR-LT-M50 | 32.0 | 38.0 | M50 x 1.5 | 15.0 | 52.0 | 57.0 |
| GripLoc-BR-LT-M63 | 37.0 | 44.0 | M63 x 1.5 | 15.0 | 53.0 | 68.0 |

Call the Remora sales team at 01226 352 000

Challenge us - We find a solution