

Cable Glands | GRIPLOC® METALLIC CABLE GLANDS

GRIPLOC® BRASS CABLE GLANDS



• Cap



• GripLoc Seal®



• Body



• Nitrile O-Ring



• Nitrile O-Ring



Multi-Hole Seals p.29



Locknuts Supplied Separately p.89

Brass GripLoc® Glands PG

- PG range of brass cable glands.
- GripLoc Seal® - Superior Ingress Protection, mechanical grip and cable retention.


Standards: EN 50262

Protection: IP69K / IP68 10 bar (150 PSI)

Temperature Range: -40°C to 100°C(static) 120°(temp)

Material (Gland): Nickel-Plated Brass

Material (Seal): NBR Seal and EPDM O-Ring



Code	Cable Range (B)		Size	Entry Thread		Gland A/F
	Min	Max		Length (L1)	Length (L2)	
GripLoc-BR-LT-PG7	2.0	5.0	PG7 x 1.27	10.0	29.0	14.0
GripLoc-BR-LT-PG9	4.0	8.0	PG9 x 1.41	10.0	31.0	17.0
GripLoc-BR-LT-PG11	5.0	10.0	PG11 x 1.41	10.0	32.0	20.0
GripLoc-BR-LT-PG13.5	6.0	12.0	PG13.5 x 1.41	10.0	33.0	22.0
GripLoc-BR-LT-PG16	10.0	14.0	PG16 x 1.41	10.0	34.0	24.0
GripLoc-BR-LT-PG21	13.0	18.0	PG21 x 1.59	12.0	37.0	30.0
GripLoc-BR-LT-PG29	18.0	25.0	PG29 x 1.59	12.0	43.0	40.0
GripLoc-BR-LT-PG36	22.0	32.0	PG36 x 1.59	15.0	52.0	50.0
GripLoc-BR-LT-PG42	32.0	38.0	PG42 x 1.59	15.0	52.0	57.0
GripLoc-BR-LT-PG48	37.0	44.0	PG48 x 1.59	15.0	53.0	64.0

GripLoc® brand cable glands are offered for sale exclusively in the United Kingdom by Remora Electrical Limited.